



Drill Size Decimal Equivalent

Drill Size	MM	Decimal Equivalent	Drill Size	MM	Decimal Equivalent	Drill Size	MM	Decimal Equivalent	Drill Size	MM	Decimal Equivalent	Drill Size	MM	Decimal Equivalent
-	0.10	0.0039	53	1.51	0.0595	-	4.00	0.1575	J	7.04	0.2770	-	14.00	0.5512
-	0.20	0.0079	1/16	1.59	0.0625	21	4.04	0.1590	K	7.14	0.2810	9/16	14.29	0.5625
-	0.25	0.0098	52	1.61	0.0635	20	4.09	0.1610	9/32	7.14	0.2812	37/64	14.68	0.5781
-	0.30	0.0118	51	1.70	0.0670	19	4.22	0.1660	L	7.37	0.2900	-	15.00	0.5906
80	0.34	0.0135	50	1.78	0.0700	18	4.31	0.1695	M	7.49	0.2950	19/32	15.08	0.5938
79	0.37	0.0145	49	1.85	0.0730	11/64	4.37	0.1719	19/64	7.54	0.2969	39/64	15.48	0.6094
1/64	0.40	0.0156	48	1.93	0.0760	17	4.39	0.1730	N	7.67	0.3020	5/8	15.88	0.6250
78	0.41	0.0160	5/64	1.98	0.0781	16	4.50	0.1770	5/16	7.94	0.3125	-	16.00	0.6299
77	0.46	0.0180	47	1.99	0.0785	15	4.57	0.1800	-	8.00	0.3150	41/64	16.27	0.6406
-	0.50	0.0197	-	2.00	0.0787	14	4.62	0.1820	O	8.03	0.3160	21/32	16.67	0.6562
76	0.51	0.0200	46	2.06	0.0810	13	4.70	0.1850	P	8.20	0.3230	-	17.00	0.6693
75	0.53	0.0210	45	2.08	0.0820	3/16	4.76	0.1875	21/64	8.33	0.3281	43/64	17.07	0.6719
74	0.57	0.0225	44	2.18	0.0860	12	4.80	0.1890	Q	8.43	0.3320	11/16	17.46	0.6875
-	0.60	0.0236	43	2.26	0.0890	11	4.85	0.1910	R	8.61	0.3390	45/64	17.86	0.7031
73	0.61	0.0240	42	2.37	0.0935	10	4.91	0.1935	11/32	8.73	0.3438	-	18.00	0.7087
72	0.64	0.0250	3/32	2.38	0.0938	9	4.98	0.1960	S	8.84	0.3480	23/32	18.26	0.7188
71	0.66	0.0260	41	2.44	0.0960	-	5.00	0.1968	-	9.00	0.3543	47/64	18.65	0.7344
-	0.70	0.0276	40	2.50	0.0980	8	5.05	0.1990	T	9.09	0.3580	-	19.00	0.7480
70	0.71	0.0280	39	2.53	0.0995	7	5.11	0.2010	23/64	9.13	0.3594	3/4	19.05	0.7500
69	0.74	0.0292	38	2.58	0.1015	13/64	5.16	0.2031	U	9.35	0.3680	49/64	19.45	0.7656
-	0.75	0.0295	37	2.64	0.1040	6	5.18	0.2040	3/8	9.53	0.3750	25/32	19.84	0.7812
68	0.79	0.0310	36	2.71	0.1065	5	5.22	0.2055	V	9.56	0.3770	-	20.00	0.7874
1/32	0.79	0.0313	7/64	2.78	0.1094	4	5.31	0.2090	W	9.80	0.3860	51/64	20.24	0.7969
-	0.80	0.0315	35	2.79	0.1100	3	5.41	0.2130	25/64	9.92	0.3906	13/16	20.64	0.8125
67	0.81	0.0320	34	2.82	0.1110	7/32	5.56	0.2188	-	10.00	0.3937	-	21.00	0.8268
66	0.84	0.0330	33	2.87	0.1130	2	5.61	0.2210	X	10.08	0.3970	53/64	21.03	0.8281
65	0.89	0.0350	32	2.95	0.1160	1	5.79	0.2280	Y	10.26	0.4040	27/32	21.43	0.8438
-	0.90	0.0354	-	3.00	0.1181	A	5.94	0.2340	13/32	10.32	0.4062	55/64	21.84	0.8594
64	0.91	0.0360	31	3.05	0.1200	15/64	5.95	0.2344	Z	10.49	0.4130	-	22.00	0.8661
63	0.94	0.0370	1/8	3.18	0.1250	-	6.00	0.2362	27/64	10.72	0.4219	7/8	22.23	0.8750
62	0.97	0.0380	30	3.26	0.1285	B	6.05	0.2380	-	11.00	0.4331	57/64	22.62	0.8906
61	0.99	0.0390	29	3.45	0.1360	C	6.15	0.2420	7/16	11.11	0.4375	-	23.00	0.9055
-	1.00	0.0394	28	3.57	0.1405	O	6.25	0.2460	29/64	11.51	0.4531	29/32	23.02	0.9062
60	1.02	0.0400	9/64	3.57	0.1406	1/4	6.35	0.2500	15/32	11.91	0.4688	59/64	23.42	0.9219
59	1.04	0.0410	27	3.66	0.1440	E	6.35	500	-	12.00	0.4724	15/16	23.81	0.9375
58	1.07	0.0420	26	3.73	0.1470	F	6.53	0.2570	31/64	12.30	0.4844	-	24.00	0.9449
57	1.09	0.0430	25	3.80	0.1495	G	6.63	0.2610	1/2	12.70	0.5000	61/64	24.21	0.9531
56	1.18	0.0456	24	3.86	0.1520	17/64	6.75	6	-	13.00	0.5118	31/32	24.61	0.9688
3/64	1.19	0.0469	23	3.91	0.1540	H	6.76	0	33/64	13.10	0.5156	-	25.00	0.9842
55	1.32	0.0520	5/32	3.97	0.1562	I	6.91	0.2720	17/32	13.49	0.5312	63/64	25.00	0.9844
54	1.40	0.0550	22	3.99	0.1570	-	7.00	0.2756	35/64	13.89	0.5469	1	25.40	1.0000

This technical information is supplied as a courtesy. All-Pro Fasteners, Inc. neither employs nor maintains an engineering or technical staff, and All-Pro is merely supplying certain manufacturing, technical, and/or design specifications and data received by All-Pro Fasteners, Inc. from the products' manufacturer or taken from consensus standards, and is in no manner originated, developed, created, enhanced, altered, or approved by All-Pro Fasteners, Inc.