

## HSS Connections

The range consists of the legendary Hollo-Bolt® and Lindibolt®, creating simple, cost-effective connections of HSS and other hollow sections, or conventional steel where access is available from one side only. The Hollo-Bolt® can be used as a primary structural connection as detailed in the SCI/ BCSA publication 'Joints in Steel Construction - Simple Connections'.

Model Number	Dimensions	Description
Type HB - Hollo-Bolt® Button Head Security	M8 – M12 (5/16" – 1/2")	Steel, Bright zinc plated plus JS 500; Steel, sheraplex; Stainless steel grade 316
Type HB - Hollo-Bolt® Countersunk	M8 – M16 (5/16" – 1/2")	Steel, Bright zinc plated plus JS 500; Steel, sheraplex; Stainless steel grade 316
Type HB - Hollo-Bolt® Flush Fit	M8 – M12 (5/16" – 1/2")	Steel, Bright zinc plated plus JS 500; Steel, sheraplex; Stainless steel grade 316
Type HB - Hollo-Bolt® Hexagonal Head	M8 – M20 (5/16" – 3/4")	Steel, Bright zinc plated plus JS 500; Steel, hot dip galvanized; Steel, sheraplex; Stainless steel grade 316
Type LB2 - Lindibolt® 2	M10 – M24 (3/8" – 1")	Steel, Bright zinc plated; Stainless steel grade 316