



## Thread Pitch Chart

Nominal Size, Threads per inch and Thread Series		A <sub>s</sub>	A <sub>r</sub>	A <sub>s</sub>		A <sub>s</sub> <sub>n</sub>	
		Tensile Stress Area sq. in.	Thread Root Area sq. in.	Thread Stripping Areas sq. in. per in. of Engagement			
				External Thread		Internal Thread	
				Class 2A	Class 3A	Class 2B	Class 3B
0 - 80	UNF	0.00180	0.00151	0.0673	0.0748	0.106	0.116
1 - 64	UNC	0.00263	0.00218	0.0835	0.0913	0.133	0.144
1 - 72	UNF	0.00278	0.00237	0.0831	0.0922	0.130	0.142
2 - 56	UNC	0.00370	0.00310	0.101	0.109	0.162	0.174
2 - 64	UNF	0.00394	0.00339	0.101	0.110	0.156	0.170
3 - 48	UNC	0.00487	0.00406	0.118	0.127	0.191	0.204
3 - 56	UNF	0.00523	0.00451	0.118	0.130	0.186	0.201
4 - 40	UNC	0.00604	0.00496	0.138	0.147	0.221	0.235
4 - 48	UNF	0.00661	0.00566	0.140	0.151	0.216	0.232
5 - 40	UNC	0.00796	0.00672	0.161	0.172	0.248	0.263
5 - 44	UNF	0.00830	0.00716	0.162	0.173	0.246	0.262
6 - 32	UNC	0.00909	0.00745	0.180	0.189	0.281	0.296
6 - 40	UNF	0.01015	0.00874	0.182	0.197	0.274	0.292
8 - 32	UNC	0.0140	0.0120	0.226	0.239	0.334	0.353
8 - 36	UNF	0.0147	0.0128	0.227	0.244	0.331	0.350
10 - 24	UNC	0.0175	0.0145	0.263	0.227	0.401	0.420
10 - 32	UNF	0.0200	0.0175	0.275	0.289	0.389	0.411
12 - 24	UNC	0.0242	0.0206	0.312	0.327	0.458	0.478
12 - 28	UNF	0.0258	0.0226	0.317	0.336	0.450	0.474
1/4 - 20	UNC	0.0318	0.0269	0.368	0.385	0.539	0.563
1/4 - 28	UNF	0.0364	0.0326	0.373	0.403	0.521	0.549
5/16 - 18	UNC	0.0524	0.0454	0.470	0.502	0.682	0.710
5/16 - 24	UNF	0.0580	0.0524	0.479	0.520	0.663	0.696
3/8 - 16	UNC	0.0775	0.0678	0.576	0.619	0.828	0.860
3/8 - 24	UNF	0.0878	0.0809	0.578	0.644	0.800	0.387
7/16 - 14	UNC	0.106	0.0933	0.677	0.734	0.981	1.01
7/16 - 20	UNF	0.119	0.109	0.685	0.761	0.908	0.991
1/2 - 13	UNC	0.142	0.126	0.779	0.854	1.12	1.16
1/2 - 20	UNF	0.160	0.149	0.799	0.887	1.08	1.13
9/16 - 12	UNC	0.182	0.162	0.893	0.974	1.27	1.32
9/16 - 18	UNF	0.203	0.189	0.901	1.02	1.23	1.29
5/8 - 11	UNC	0.226	0.202	0.998	1.09	1.42	1.47
5/8 - 18	UNF	0.256	0.240	0.998	1.13	1.37	1.43
3/4 - 10	UNC	0.334	0.302	1.21	1.34	1.72	1.78
3/4 - 16	UNF	0.373	0.351	1.23	1.38	1.66	1.73
7/8 - 9	UNC	0.462	0.419	1.43	1.58	2.03	2.09
7/8 - 14	UNF	0.0509	0.480	1.44	1.63	1.96	2.03
1 - 8	UNC	0.606	0.551	1.66	1.82	2.33	2.40
1 - 12	UNF	0.663	0.625	1.66	1.87	2.27	2.35
1 - 14	UNS	0.680	0.646	1.67	1.89	2.23	2.33
1-1/8 - 6	UNC	0.763	0.693	1.88	2.04	2.65	2.72
1-1/8 - 8	UN	0.790	0.728	1.89	2.07	2.63	2.70
1-1/4 - 7	UNC	0.969	0.890	2.11	2.30	2.94	3.02
1-1/4 - 8	UN	1.000	0.929	2.12	2.33	2.92	3.00
1-3/8 - 6	UNC	1.16	1.05	2.34	2.52	3.27	3.35
1-3/8 - 8	UN	1.23	1.16	2.34	2.58	3.21	3.30
1-1/2 - 6	UNC	1.41	1.29	2.58	2.77	3.57	3.65
1-1/2 - 8	UN	1.49	1.41	2.57	2.84	3.50	3.61
1-5/8 - 8	UN	1.78	1.68	2.80	3.10	3.79	3.91
1-3/4 - 5	UNC	1.90	1.74	3.04	3.24	4.20	4.30
1-3/4 - 8	UN	2.08	1.98	3.03	3.35	4.08	4.21
1-7/8 - 8	UN	2.41	2.30	3.25	3.63	4.37	4.50

This technical information is supplied as a courtesy. All-Pro Fasteners, Inc. neither employs nor maintains an engineering or technical staff, and All-Pro is merely supplying certain manufacturing, technical, and/or design specifications and data received by All-Pro Fasteners, Inc. from the products' manufacturer or taken from consensus standards, and is in no manner originated, developed, created, enhanced, altered, or approved by All-Pro Fasteners, Inc.